



AC - 55 **WATER DILUTABLE – HEAVY DUTY - BIODEGRADABLE EXTERIOR AIRCRAFT SURFACE CLEANER**

DESCRIPTION

AC-55 is a concentrated, water based, liquid compound, which meets the requirements of BOEING Document D6 – 17487, MIL-C-25769, AMS-1526C and ARP-1512A.

APPLICATION

AC-55 is used for the exterior cleaning of painted or unpainted aircraft surfaces, aerospace equipment, aerospace ground equipment and AGE engines. Removes efficiently all kind of dirt such as oil, grease, mud, smoke, etc.

It is safe for all kind of metals and does not attack paint coatings.

USAGE

AC-55 can be applied by brush or spray. Normally AC-55 is used diluted 1 part up to 10 parts of water depending on the type and quantity of soil involved.

- a) For heavy duty cleaning: Dilute 1 part of the product up to 3 parts of water.
- b) For normal cleaning: Dilute 1 part of the product up to 5 parts of water.
- c) For light cleaning: Dilute 1 part of the product up to 10 parts of water.

Allow to stand for approximately 5-15 minutes.

Brush all areas with stiff bristle brush and finally rinse with high-pressure water.

PRODUCT PROPERTIES

Appearance:	Clear liquid
Boiling point:	100 °C
Solubility in water:	Complete in all proportions
Specific gravity:	1,020 ± 0,02 gr/cm ³
Flash point:	None to boil.

SAFETY

AC-55 is an alkaline material. Avoid contact with skin and eyes. For further instructions refer to analytical Material Safety Data Sheet.

PACKAGING

AC-55 is available in 210 Lt drums.