

**CORROSION PREVENTIVE N° 2**  
**(MIL-PRF-16173E CLASS II, GRADE 2)**  
**(Low V.O.C.)**

**Corrosion Preventive Compound,  
Water Displacing, Soft Film  
Protects Metals Against Rust and  
Corrosion for Indoor Storage**

**Description:**

**CORROSION PREVENTIVE N° 2** is a corrosion preventive compound specially designed to protect metals against rust and corrosion for indoor storage, semi-sheltered outdoor storage and shipment. When used as recommended **CORROSION PREVENTIVE N° 2** is easy and economical to apply and provides a durable, long lasting, soft coating suitable for protecting metal surfaces against the elements of corrosive environment.

**Advantages:**

- ◆ Forms a corrosion resistant and salt water resistant protective film.
- ◆ Stops grinding by penetrating deep and lubricating, hinges, locks, mechanisms, threads, etc.
- ◆ After its application surfaces remain lubricated.
- ◆ Meets corrosion requirements of U.S. Military Specification MIL-PRF-16173E CLASS II, GRADE 2 soft film.
- ◆ Keeps moisture away.

**Intended Usage:**

a) For extended indoor protection of interior or exterior surfaces of machinery, instruments, bearings or materials with or without use of supplementary barrier materials.

b) For outdoor protection of material for limited periods where metal temperatures do not reach levels that produce prohibitive flow of the corrosion preventive film.

c) For use where water or saline solution must be displaced from corrodible surfaces and the corrosion prevented or arrested.

d) Maintenance protection of on-site plant and equipment.

e) Preservation, high protection of gas turbine compressors.

**Alternative Usage:**

**CORROSION PREVENTIVE N° 2** can also be used for electric motors, outboard engines, distributors, spark plugs, relays, etc.

**Directions for Use:**

**CORROSION PREVENTIVE N° 2** is used in full strength by spray, immersion or swab. Allow **CORROSION PREVENTIVE N° 2** to dry to form a soft, protective anti-corrosive film.

**Product Removal:**

**CORROSION PREVENTIVE N° 2** is easily removed from parts by solvent wiping, steam gun cleaning or alkaline hot tank immersion.

**Caution:**

Avoid contact with skin and eyes. For further information refer to Material Safety Data Sheet (MSDS).

**Packaging:**

**CORROSION PREVENTIVE N° 2** is offered in 4, 13, 20, 30 liter pails or 210 liter drums.