

## **K – 2015 AP**

### **THE MOST EFFECTIVE PAINT REMOVER**

### **ACID ACTIVATED FOR AMINE-CURED EPOXY COATING SYSTEMS**

#### **Description**

**K-2015 AP** is a viscous, acid activated, water rinseable, aircraft paint stripper, which meets the requirements of MIL-R-81903A TYPE II, class 1.

#### **Application**

**K-2015 AP** is especially designed for removing mainly polyurethane, epoxy paints and other highly resistant coatings where traditional paint removers have poor results.

Since the product is of a viscous nature, it is ideal for use on vertical or inclined surfaces.

**K-2015 AP** is not corrosive to most of metals such as Aluminum, Titanium, Cadmium plated steels etc. Do not use **K-2015 AP** on Magnesium and Magnesium alloys.

#### **Advantages**

- The most effective paint remover used where traditional paint removers have poor results.
- Non-flammable.
- Easily rinsed with cold water.
- Can be applied by brush or non-atomizing spray methods.
- Used as received. No mixing or dilution required.
- Used at room temperature.

#### **Usage**

**K-2015 AP** can be applied as received by brush or spray. Because it is thick it is ideal for vertical surfaces.

Allow **K-2015 AP** sufficient dwell time for thorough loosening or blistering of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush. The complete removal of the paint residues is accomplished with high pressure, high volume, cold water or with a steam cleaning machine.

Normally a coat of **K-2015 AP** is sufficient to remove more than one coating of paint.

#### **Safety**

**K-2015 AP** contains chlorinated hydrocarbons and phenolic bodies. Avoid contact with skin, eyes and clothing. Gloves, goggles, face shields are recommended when handling. For further information refer to Material Safety Data Sheet.

#### **Packaging**

**K-2015 AP** is available in 250 kg drums.