

K – 2015 NP

VERY EFFECTIVE PAINT REMOVER

ACID ACTIVATED FOR AMINE-CURED EPOXY COATING SYSTEMS

Description

K-2015 NP is a viscous, acid activated, non-phenolic water rinseable, aircraft paint stripper, which meets the requirements of MIL-R-81903A TYPE II, class 2.

Application

K-2015 NP is especially designed for removing mainly polyurethane, epoxy paints and other highly resistant coatings where traditional paint removers have poor results.

Since the product is of a viscous nature, it is ideal for use on vertical or inclined surfaces.

K-2015 NP is not corrosive to most of metals such as Aluminum, Titanium, Cadmium plated steels etc. Do not use **K-2015 NP** on Magnesium and Magnesium alloys.

Advantages

- ˆ The most effective paint remover used where traditional paint removers have poor results.
- ˆ Non-flammable.
- ˆ Easily rinsed with cold water.
- ˆ Can be applied by brush or non-atomizing spray methods.
- ˆ Used as received. No mixing or dilution required.
- ˆ Used at room temperature.

Usage

K-2015 NP can be applied as received by brush or spray. Because it is thick it is ideal for vertical surfaces.

Allow **K-2015 NP** sufficient dwell time for thorough loosening or blistering of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush. The complete removal of the paint residues is accomplished with high pressure, high volume, cold water or with a steam cleaning machine.

Normally a coat of **K-2015 NP** is sufficient to remove more than one coating of paint.

Safety

K-2015 NP contains chlorinated hydrocarbons and inorganic acids. Avoid contact with skin, eyes and clothing. Gloves, goggles, face shields are recommended when handling. For further information refer to Material Safety Data Sheet.

Packaging

K-2015 NP is available in 250 kg drums.