

S-2099 **(NON-PHENOLIC PAINT STRIPPER)**

Description

S-2099 is a thickened, non phenolic aircraft paint stripper which meets the requirements of BOEING Document D6-17487 and TT-R-248 B.

Application

S-2099 is a viscous liquid developed to remove multiple coats of paint. It clings to vertical as well as the underside of horizontal surfaces.

S-2099 is specially designed to remove lacquer and enamel coating finishes from metal surfaces of aircraft or other surfaces.

S-2099 is even suitable for stripping various types of paints such as varnish, zinc chromate primer, epoxy, polyurethane, etc.

Advantages

- Safe to all metals.
- Very effective, normally removes more than one coating of paint.
- Non-flammable.
- Free of phenolics.
- Easily rinsed with cold water.
- Can be applied by brush or non-atomizing spray methods.
- Used as received. No mixing or dilution required.
- Used at room temperature.

Usage

S-2099 can be applied as received by brushing or spraying. Because of it is thick is ideal for vertical surfaces.

Allow **S-2099** sufficient dwell time for thorough loosening or blistering of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush. The complete removal of the paint residues is accomplished with high pressure, high volume, cold water or with a steam cleaning machine.

Normally one coat of **S-2099** is sufficient to remove more than one paint coating.

Where multicoat systems have to be removed, it may be necessary to use more than one application of **S-2099**.

Safety

S-2099 contains chlorinated solvents, chromates and ammonium hydroxide. Avoid contact with skin, eyes and clothing. Gloves, goggles, face shields are recommended when handling. For further information refer to Material Safety Data Sheet.

Packaging

S-2099 is available in 55 gallon drums.