



## PICKLING PASTE

**Viscous liquid for cleaning welded surfaces of stainless steel objects.**

### Description

**PICKLING PASTE** is a viscous liquid product (paste) specially designed for removing carbon deposits from welded surfaces of stainless steel objects and generally all stainless steel surfaces.

### Advantages

- Suitable for all types of stainless steel.
- Viscous: ideal for vertical surfaces.
- Very effective.
- Very economical because it is applied only to the area that requires pickling.

### Usage

**PICKLING PASTE** is used by brush or Injection.

Contact time 30-180 minutes depending on the Thickness of the coating and the conditions of the weather.

Consumption: 1 kilogram covers a surface of 2-4 m<sup>2</sup>

Rinse with water under pressure or clean with a wet sponge.

### Physical Properties

|               |                         |
|---------------|-------------------------|
| Appearance :  | Viscous liquid          |
| pH :          | < 1                     |
| Coating :     | 2-4 m <sup>2</sup> / KG |
| Contact time: | 30-180 minutes.         |

### Caution

**PICKLING PASTE** is an acidic product and all necessary precautions should be taken. The use of protective goggles and gloves is recommended. Avoid contact with skin and eyes. In case of contact rinse with plenty of water. For further instructions refer to Material Safety Data Sheet.

### Packaging

**PICKLING PASTE** is available in 1, 2 and 5 kilogram pails.

